

STANDARD

STORED PRESSURE FIRE EXTINGUISHERS



- **SODIUM BICARBONATE** based dry chemical agent capable of fighting Class "B" and "C" type fires.
- The original and least expensive type of dry chemical often selected for training programs.
- **Ideal Uses:** Kitchens, garages, vehicles and boats.

SPECIFICATIONS	100 PSI OPERATING PRESSURE			195 PSI OPERATING PRESSURE			
	2-STD V/B	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD TALL	10 STD SHORT	20 STD
Picture No.	1	2	3	4	5	6	7
Part No. Alum Valve	18111	13115	11014	13514	11845	11810	12220
Part No. Brass Valve	-	-	11015	13515	11846	-	-
Capacity (Lbs.)	2	2.5	5.5	5.5	10	10	20
U.L. Rating	5 B:C	10 B:C	40 B:C	40 B:C	40 B:C	40 B:C	120 B:C
Ship Wt. (Lbs.) Alum. Valve	3 ¹ / ₄	4	10	10 ¹ / ₄	17 ¹ / ₂	17 ³ / ₄	33
Ship Wt. (Lbs.) Brass Valve	-	-	10 ¹ / ₂	10 ³ / ₄	18	-	-
Height (Inches)	13 ¹ / ₂	15 ³ / ₄	16 ³ / ₈	16 ³ / ₈	18	16 ³ / ₄	21 ³ / ₁₆
Width (Inches)	4 ¹ / ₂	4 ¹ / ₂	7 ¹ / ₄	7 ¹ / ₄	8	8 ¹ / ₄	8 ³ / ₄
Diameter (Inches)	2 ⁷ / ₈	3	4 ⁹ / ₃₂	4 ⁹ / ₃₂	5 ¹¹ / ₁₆	6	7 ¹ / ₂
Bracket	VEH/MAR	VEH/MAR	WALL	VEH/MAR	WALL	WALL	WALL
Range (Ft.)	9-15	9-15	12-18	12-18	15-21	15-21	15-21
Discharge Times (Sec.)	9	9	14	14	14	14	26
Cylinder	Aluminum	Aluminum	Steel	Steel	Steel	Steel	Steel
USCG Approved - Yes	Type B:C Size I			Type B:C Size II		Type B:C Size III	