

HALOTRON™ I WHEELED EXTINGUISHERS

STORED PRESSURE



MODEL W-65 HALOTRON™ I



MODEL W-150 HALOTRON™ I

IDEAL USES: Computers, telephone switch gear, sensitive data storage areas, offices, boats, forest machines, aircraft flight lines, and mobile units. The 150 Lb. unit is FAA approved for airport crash trucks.

SPECIFICATIONS

MODEL NUMBER	W-65 HALOTRON™ I	W-150 HALOTRON™ I
Part Number	76500	71500
Agent	HALOTRON™ I	
Capacity LBS./KG	65/29.5	150/68
U.L. Rating	4A:40B:C	10A:80B:C
Operating Temp.	°F -40° to + 120° °C -40° to + 49°	
Argon Charge	PSI 125 kPa 862.5	
Hose Length	FT 25 M 7.62	FT 40 M 12.19
Hose Diameter	IN 3/4 CM 1.90	IN 1 CM 2.54
Wheels	IN 16 x 4 CM 40.64 x 10.16	
Height	IN 50 CM 127	IN 62 CM 157.5
Width	IN 24 CM 60.96	IN 24 CM 60.96
Depth	IN 41.5 CM 105.41	IN 41.5 CM 105.41
Shipping Weight	LBS 300 KG 136	LBS 480 KG 218
Cyl. Test Pressure	LBS 480 kPa 1656	
Cyl. Burst Pressure	LBS 1200 Minimum kPa 8280 Minimum	
Discharge Time (SEC.)	17	23
Discharge Range	FT 15 - 25 M 4.57 - 7.62	FT 23 - 35 M 7.62 - 10.67
USCG Approval	N/A	N/A

FEATURES

- DOT approved cylinders with chrome plated brass valve assemblies. Cylinders are manufactured to DOT specification 4BW240 Valves are designed and manufactured to Buckeye's rigid standard of quality.
- Highly visible pressure-indicating gauge.
- Cylinders and carriages are shot blasted, primed and coated with the finest polyurethane powder paint finish that exceeds Underwriter's Laboratories salt spray requirements.
- Tow loops are available upon request for the 65 Lb. unit and standard on the 150 Lb. unit.
- All booster hoses are Underwriter's Laboratories listed coupled with brass chrome plated fittings. Hose lengths are as shown in the specification chart.
- All units are equipped with all weather semi-pneumatic 16 in. diameter, 4 in. wide tires that allows for easy moveability through narrow doors and walkways by a single operator.
- Built to ANSI/UL 2129 and ANSI/UL 711 standards.
- Stationary units are also available similar to above less wheels and tow loop.