



PURPLE K

STORED PRESSURE FIRE EXTINGUISHERS



- **POTASSIUM BICARBONATE** based dry chemical agent capable of fighting Class “B” and “C” type fires.
- The most effective type of dry chemical on Class “B” fires.
- **Ideal Uses:** Garages, service bays, boats, vehicles, fuel storage and transfer areas.

SPECIFICATIONS	100 PSI OPERATING PRESSURE				195 PSI OPERATING PRESSURE			
	2 PK V/B	2.5 PK V/B	5 PK	5 PK V/B	10 PK TALL	10 PK SHORT	20 PK	30 PK
SIZE/MODEL	2 PK V/B	2.5 PK V/B	5 PK	5 PK V/B	10 PK TALL	10 PK SHORT	20 PK	30 PK
Picture No.	1	2	3	4	5	6	7	8
Part No. Alum Valve	19121	13215	11214	25914	11745	11710	12620	–
Part No. Brass Valve	–	–	11215	25915	11746	–	12621	12805
Capacity (Lbs.)	2	2.5	5	5	10	10	20	30
U.L. Rating	5 B:C	10 B:C	20 B:C	20 B:C	80 B:C	80 B:C	120B:C	160 B:C
Ship Wt. (Lbs.) Alum. Valve	3 ¹ / ₄	4	9 ¹ / ₂	9 ³ / ₄	17 ¹ / ₂	17 ³ / ₄	33	–
Ship Wt. (Lbs.) Brass Valve	–	–	10	10 ¹ / ₄	18	–	33 ¹ / ₂	52 ¹ / ₄
Height (Inches)	13 ¹ / ₂	15 ³ / ₄	16 ³ / ₈	16 ³ / ₈	18	16 ³ / ₈	21 ³ / ₁₆	27 ⁵ / ₁₆
Width (Inches)	4 ¹ / ₂	4 ¹ / ₂	7 ¹ / ₄	7 ¹ / ₄	8	8 ¹ / ₄	8 ³ / ₄	8 ³ / ₄
Diameter (Inches)	2 ⁷ / ₈	3	4 ⁹ / ₃₂	4 ⁹ / ₃₂	5 ¹¹ / ₁₆	6	7 ¹ / ₂	7 ¹ / ₂
Bracket	VEH/MAR	VEH/MAR	WALL	VEH/MAR	WALL	WALL	WALL	WALL
Range (Ft.)	9-15	9-15	12-18	12-18	15-21	15-21	15-21	25-30
Discharge Times (Sec.)	9	9	9	9	22	22	26	32
Cylinder	Aluminum	Aluminum	Steel	Steel	Steel	Steel	Steel	Steel
USCG Approved	yes		Type B,C Size I		Type B,C Size II		Type B,C Size III	Type B,C Size IV