

ABC MULTI-PURPOSE

STORED PRESSURE FIRE EXTINGUISHERS



- **MONOAMMONIUM PHOSPHATE** based dry chemical agent capable of fighting Class "A," "B" and "C" type fires.
- This agent provides the widest and most practical range of extinguisher fire protection coverage.
- **Ideal Uses:** Homes, office buildings, warehouses, farms, woodworking areas

(*Note—not recommended for use on expensive delicate equipment or computers.)

SPECIFICATIONS	100 PSI OPERATING PRESSURE					195 PSI OPERATING PRESSURE					
	2.5 ABC	2.5 ABC V/B	4 ABC	4 ABC V/B	5 ABC	5 ABC V/B	10 ABC TALL	10 ABC TALL	10 ABC SHORT	20 ABC	30 ABC
Picture No.	1	2	3	4	5	6	7	8	9	10	11
Part No. Alum Valve	10015	13015	10705	13705	10914	25614	11340	11345	11310	12120	—
Part No. Brass Valve	—	—	—	—	10915	25615	11341	11346	—	12121	12905
Capacity (Lbs.)	2.5	2.5	4	4	5	5	10	10	10	20	30
U.L. Rating	1A:10B:C	1A:10B:C	2A:10B:C	2A:10B:C	3A:40B:C	3A:40B:C	4A:80B:C	4A:80B:C	4A:60B:C	20A:120B:C	20A:160B:C
Ship Wt. (Lbs.) Alum. Valve	3 ³ / ₄	4	6 ¹ / ₂	6 ³ / ₄	9 ¹ / ₂	9 ³ / ₄	—	17 ¹ / ₂	17 ³ / ₄	33	—
Ship Wt. (Lbs.) Brass Valve	—	—	—	—	10	10 ¹ / ₄	18 ¹ / ₄	18	—	33 ¹ / ₂	52 ¹ / ₄
Height (Inches)	15 ³ / ₄	15 ³ / ₄	16 ¹ / ₂	16 ¹ / ₂	16 ³ / ₈	16 ³ / ₈	21	18	16 ³ / ₄	21 ³ / ₁₆	27 ⁵ / ₁₆
Width (Inches)	4 ¹ / ₂	4 ¹ / ₂	6 ¹ / ₄	6 ¹ / ₄	7 ¹ / ₄	7 ¹ / ₄	7 ³ / ₄	8	8 ¹ / ₄	8 ³ / ₄	8 ³ / ₄
Diameter (Inches)	3	3	3 ¹ / ₂	3 ¹ / ₂	4 ⁹ / ₃₂	4 ⁹ / ₃₂	5 ¹ / ₈	5 ¹ / ₁₆	6	7 ¹ / ₂	7 ¹ / ₂
Bracket	WALL	VEH/MAR	WALL	MAR	WALL	VEH/MAR	WALL	WALL	WALL	VEH/MAR	VEH/MAR
Range (Ft.)	9-15	9-15	9-15	9-15	12-18	12-18	15-21	15-21	15-21	15-21	25-30
Discharge Times (Sec.)	9	9	14	14	14	14	22	22	18	26	32
Cylinder	Aluminum	Aluminum	Aluminum	Aluminum	Steel	Steel	Steel	Steel	Steel	Steel	Steel
USCG Approved – Yes	Type B:C Size I				Type A Size II Type B:C Size I		Type A Size II Type B:C Size II			Type A Size II Type B:C Size III	Type A Size II Type B:C Size IV